

Références produit SwissHydro		Diamètre	Pression d'eau (bar)	Limite de température (°C)	Débit (m3/h)	Perte de charge (bar)	Poids (kg)	Hauteur (mm)	Diamètre	Longueur d'installation (mm)
HydroCare D20		3/4" - DN20	12	1-95	8,28	0,2	5	210	0	140
HydroCare D25		1" - DN25	12	1-95	12,24	0,2	5	210	0	140
HydroCare D32		1 1/4" - DN32	12	1-95	20,16	0,2	13,3	340	0	150
HydroCare D40		1 1/2" - DN40	12	1-95	24,48	0,2	13,3	340	0	190
HydroCare D50		2" - DN50	12	1-95	36	0,2	26	445	0	220
HydroCare D65B		2 1/2" - DN65	12	1-95	46,08	0,2	45	520	0	220
HydroCare D80B		3" - DN80	12	1-95	54	0,2	45	520	0	250
HydroCare D100B		4" - DN100	12	1-95	76,68	0,2	65	570	0	290
HydroCare S15		1/2" - DN15	12	1-95	1,8	0,25	0,6	0	40	125
HydroCare S20		3/4" - DN20	12	1-95	2,88	0,25	0,6	0	40	125
HydroCare S25		1" - DN25	12	1-96	4,68	0,25	0,85	0	60	150
HydroCare S32		1 1/4" - DN32	12	1-97	7,56	0,25	3,2	0	60	150
HydroCare S40		1 1/2" - DN40	12	1-98	10,8	0,25	4,3	0	76	200
HydroCare S50		2" - DN50	12	1-99	17,28	0,25	5	0	88	200

Références produit SwissHydro		Dimension (pouce)	Débit (m3/h)	Longueur d'installation (mm)	Diamètre	Poids (kg)	Perte de charge (bar)	Diamètre nominal (DN)
HydroClean 40P		1 1/2"	10,08	144	90	2	0,20	DN40
HydroClean 50B		2"	15,12	320	170	9,5	0,20	DN50
HydroClean 65B		2,5"	25,2	320	185	11	0,20	DN65
HydroClean 80B		3"	29,88	340	200	13,5	0,20	DN80
HydroClean 100B		4"	59,76	370	220	17	0,20	DN100
HydroClean 150B		6"	135	476	285	30,5	0,20	DN150
HydroClean 200B		8"	230,4	590	340	46,5	0,20	DN200
HydroClean 250B		10"	365,04	700	405	69	0,20	DN250
HydroClean 15		½"	1,8	125	40	0,60	0,25	DN15
HydroClean 20		¾"	2,88	125	40	0,60	0,25	DN20
HydroClean 25		1"	4,68	150	60	0,85	0,25	DN25
HydroClean 32		1"1/4	7,56	150	60	3,20	0,25	DN32
HydroClean 40		1"1/2	10,8	200	76	4,30	0,25	DN40
HydroClean 50		2"	17,28	200	88	5,00	0,25	DN50